


PDV & PDV-K

ALEV GECİKTİRİCİ ÖZELLİK/İNCELTİLMİŞ DIŞ ÇAP/KÜÇÜK BÜKÜLME YARIÇAPI
FLAME RETARDANT CHARACTERISTIC/REDUCED OUTER DIAMETER/SMALL BENDING RADIUS



KULLANIM ALANLARI

- Bina içi tesisatlarda;
- Telefon santralleri ve abone dağıtımlarında
- Sinyal ve data iletiminde

KABLO YAPISI

- 1-İletken** IEC 60228; DIN VDE 0295; EN 60228 Sınıf 1
Elektrolitik Bakır
2-Yalıtım Solid PE Kompaund
3-Yalıtım Renk TS EN 60708
4-Büküm 10 çiftte kadar yıldız dörtlü büküm.
10 çiftten sonra 5 yıldız dörtlü bükümü bir grup.
Ve 5 veya 10 grup bükümü bir paket;
her grup polipropilen tanıma şeridi ile sarılır
5-Ayrırıcı Bant Pes Bant (10 çift üstü)
6-Kılıf PVC Kompaund
7-Kılıf Rengi RAL 7001 Gri

APPLICATION

- At indoor installations;
- Telephone exchanges and subscriber distributions
- Signal and data transmission

CONSTRUCTION

- 1-Conductor** IEC 60228; DIN VDE 0295; EN 60228 Class 1
Electrolytic Copper
2-Insulation Solid PE Compound
3-Colour Code TS EN 60708
4-Stranding Up to 10 pairs laid up as star-quads. After 10 pairs,
5 star quads laid up to a group. And 5 or 10 groups
laid up to a unit; each group is wrapped by
polypropylene identification tape
5-Wrapping Pes Tape (more than 10 pairs)
6-Sheath PVC Compound
7-Sheath Colour RAL 7001 Grey

TEKNİK ÖZELLİKLER TECHNICAL CHARACTERISTICS

İLETKEN DİRENCİ CONDUCTOR RESISTANCE	YALITIM DİRENCİ INSULATION RESISTANCE	EFEKTİF KAPASİTE MUTUAL CAPACITANCE	ÇALIŞMA SICAKLIĞI TEMPERATURE RANGE
mm Ω/km 0,5 97,8	5000MΩxkm	56nF/km	- 30°C - +70°C
TEST VOLTAJ (DC) TEST VOLTAGE(DC)	ÇALIŞMA VOLTAJ OPERATING VOLTAGE	BÜKÜLME YARIÇAPI BENDING RADIUS	ALEV GECİKTİRİCİLİK TESTİ FLAME RETARDANT TEST
1000V	250V	7,5 x Cable Ø	IEC 60332-1-2 VDE 0482-332-1-2 EN 60332-1-2

NOTLAR NOTES

PDV: Elektrolitik Bakır İletken/PDV-K: Kalaylı Bakır İletken
Esas alınan standartlar VDE 0816/TS EN 60708
PDV: Electrolytic Copper Conductor
PDV-K: Tinned Copper Conductor
Based on VDE 0816/TS EN 60708 standards

KOD NO CODE NR.	ÇİFT SAYISI VE İLETKEN ÇAPI (mm) NUMBER OF PAIRS AND WIRE DIAMETER (mm)	KABLO ÇAPI (mm) OVERALL DIAMETER (mm)	BAKIR AĞIRLIĞI (kg/km) COPPER WEIGHT (kg/km)	YAKLAŞIK KABLO AĞIRLIĞI (kg/km) APPROX. CABLE WEIGHT (kg/km)	STANDART UZUNLUK (mt) STANDARD LENGTH (m)	
PDV	PDV-K					
342805012	342905012	1 x 2 x 0,50	3,20	6	12	100/500/1000
342805022	342905022	2 x 2 x 0,50	3,90	10	20	100/500/1000
342805032	342905032	3 x 2 x 0,50	4,50	13	25	100/500/1000
342805042	342905042	4 x 2 x 0,50	4,70	17	31	100/500/1000
342805052	342905052	5 x 2 x 0,50	5,10	20	38	100/500/1000
342805062	342905062	6 x 2 x 0,50	5,50	24	43	100/500/1000
342805102	342905102	10 x 2 x 0,50	7,30	39	75	100/500/1000
342805152	342905152	15 x 2 x 0,50	8,10	59	105	100/500/1000
342805202	342905202	20 x 2 x 0,50	9,10	77	135	100/500/1000
342805302	342905302	30 x 2 x 0,50	10,60	110	183	100/500/1000
342805502	342905502	50 x 2 x 0,50	13,20	180	300	100/500/1000
342805112	342905112	100 x 2 x 0,50	18,80	368	556	100/500/1000
342805222	342905222	200 x 2 x 0,50	25,80	726	1061	100/500